Command System Call Boxes



Part #:

2400-805SP

Dimensions:

7-1/4" x H 4-3/4" W x 1-7/8" D

Design:

Stainless Steel, Surface Mount



Part #:

2400-805SPM

Dimensions:

7-1/4" x H 4-3/4" W x 1-7/8" D

Design:

Stainless Steel, Mushroom Push Button, Surface Mount



Part #:

2400-805RP

Dimensions:

7-1/4" H x 4-3/4" W x 1-7/8" D

Design:

Red, Powder Coated, Surface Mount

Option:

Mushroom Push Button



Part #:

2400-805LP

Dimensions:

9-7/8" H x 6-5/8" W x 3-1/4" D

Design:

Red, NEMA 4, Fiberglass, Surface Mount, Exterior Rated

Option:

Mushroom Push Button



Part #:

2400-805LPC1

Call Box:

9-7/8" H x 6-5/8" W x 3-1/4" D

Cover:

6-2/5" H x 3-3/4" W x 2-1/4" D

(not ADA compliant)

Design:

Red, NEMA 4, Fiberglass, Surface Mount, Exterior Rated



Part #:

2400-808NSP

Dimensions:

9-1/2" H x 7-1/2" W

Back Box:

8" H x 6" W x 3" D

Design:

Brushed Stainless Steel,

Flush Mount

Option:

Mushroom Push Button





Command System Call Boxes



Part #:

2400-805SSPC2

Face Plate:

10" H x 6-17/25" W

Back Box:

9-7/8" H x 6-1/2" W x 3" D

Cover:

9-3/4" H x 6-1/2" W x 1-1/4" D (not ADA compliant)

Design:

Stainless Steel, Surface Mount



Part #:

2400-808SSPC2

Face Plate:

11-3/8" H x 8" W

Back Box:

9-7/8" H x 6-1/2" W x 3" D

Cover:

9-3/4" H x 6-1/2" W x 1-1/4" D

Design:

Brushed Stainless Steel, Flush Mount



Part #:

2400-808NMP

Face Plate:

9-1/2" H x 7-1/2" W

Back Box:

8" H x 6" W x 3" D

Design:

Antique Bronze, Flush Mount

Option:

Mushroom Push Button



Code Compliance

- International Building Code (IBC)
- National Fire Protection Association (NFPA)
- Americans Disabilities Act (ADA)

Power Requirements:

 Designed to be powered from the Distribution Module and requires a single pair from the Distribution Module

Phone Capabilities:

- Recordable location message (25 seconds)
- Automatic dialer (31 digit programmable memory)
- · Automatic answer feature with audible ring

Programming Features:

- Programmable with up to 2 emergency phone numbers
- On-site programming
- Recordable location message (25 seconds)
- On-site programming capability with numeric programming

