

# SmartRescue System Call Box Series



**Part #:**  
2100-956SR  
**Dimensions:**

7-1/4" H x 4-3/4" W x 1-7/8" D

**Design:**

Stainless Steel, Surface Mount

**Option:**

Strobe Interface & Relay



**Part #:**  
2100-956SRM  
**Dimensions:**

7-1/4" H x 4-3/4" W x 1-7/8" D

**Design:**

Stainless Steel, Surface Mount,  
Mushroom Push Button

**Option:**

Strobe Interface & Relay



**Part #:**  
2100-956RR  
**Dimensions:**

7-1/4" H x 4-3/4" W x 1-7/8" D

**Design:**

Red, Powder Coated,  
Surface Mount

**Options:**

Strobe Interface & Relay,  
Mushroom Push Button



**Part #:**  
2100-984LR  
**Dimensions:**

9-7/8" H x 6-5/8" W x 3-1/4" D

**Design:**

Red, NEMA 4, Fiberglass,  
Exterior Rated

**Options:**

Strobe Interface & Relay,  
Mushroom Push Button



**Part #:**  
2100-958NSR  
**Face Plate:**

9-1/2" H x 7-1/2" W

**Back Box:**

8" H x 6" W x 3" D

**Design:**

Brushed Stainless Steel, Flush  
Mount

**Options:**

Strobe Interface & Relay,  
Mushroom Push Button



**Part #:**  
2100-984LRC1  
**Call Box:**

9-7/8" H x 6-5/8" W x 3-1/4" D

**Cover:**

6-2/5" H x 3-3/4" W x 2-1/4" D  
(not ADA compliant)

**Design:**

Red, NEMA 4, Fiberglass,  
Exterior Rated

**Option:**

Strobe Interface & Relay



# SmartCommand System Call Box Series

**Part #:**

2100-956SSRC2

**Face Plate:**

10" H x 6-17/25" W

**Back Box:**

9-7/8" H x 6-1/2" W x 3" D

**Cover:**

9-3/4" H x 6-1/2" W x 1-1/4" D  
(not ADA compliant)

**Design:**

Stainless Steel, Surface Mount  
Option: Strobe Interface & Relay

**Part #:**

2100-958SSRC2

**Face Plate:**

11-3/8" H x 8" W

**Back Box:**

9-7/8" H x 6-1/2" W x 3" D

**Cover:**

9-3/4" H x 6-1/2" W x 1-1/4" D

**Design:**

Brushed Stainless Steel,  
Flush Mount

**Option:**

Strobe Interface & Relay

**Part #:**

2100-958NMBR

**Face Plate:**

9-1/2" H x 7-1/2" W

**Back Box:**

8" H x 6" W x 3" D

**Design:**

Antique Bronze, Flush Mount

**Options:**

Strobe Interface & Relay,  
Mushroom Push Button



## Code Compliance

- International Building Code (IBC)
- National Fire Protection Association (NFPA)
- Americans Disabilities Act (ADA)
- ETL Listing Number: 5013373
- Conforms to UL Standard 2017 for Attendant Monitored Signaling Devices
- Complies with Section 6.4 of UL 60950-1

## Power Requirements:

- 24vdc from part # 2500-PWR24U

## Programming Features:

- Programmable with up to 5 emergency numbers
- Recordable location message (18 seconds)
- On-site keypad programming or remote programming

## Phone Capabilities:

- Requires analog telephone line (POTS, PBX, or central office line)
- Phone checks every 24 hours for an active phone line, if one is not detected, phone will provide a relay trip
- Automatic answer feature with audible ring
- Touch Tone operation only (Touch Tone is an AT&T registered trademark)

## Additional Features:

- Compatible with SmartRescue Base Station or Command Center for in-building rescue coordination
- Built-in 10 phone consolidator feature allows you to install 10 Call Boxes and 1 Base Station on a single telephone line
- Remote or on-site diagnostic test
- Automatic dialer (31 digit programmable memory)
- 7.2V 300mAH battery (part # RP7300110)
- 2 year warranty