

# T2100 Series

T2100, T2110



Phone Enclosures Available

## Specifications:

**Dimensions:** 11.75" H x 8.5" W x 2.7" D

**Weight:** 6 lbs.

**Material:** 12 ga (0.012") brushed stainless steel

**Power:** 12-24V isolated DC, or powered from 110VAC converter provided

**Talk Battery:** 24-56VDC

**Current Range:** 11-120mA

**REN:** 1.1

**Dialing:** Tone or pulse

**Frequency Response:** 300-3,000Hz

**Operating Temperature:** -4° to 140° F (-20° to 60° C),  
23° to 122° F (-5° to 50° C) (T2100C only)

## Regulatory Standards:

- FCC Reg No: 5CDUSA-30708-AL-E
- Industry Canada No: 26817738A

## Key Features:

- Flush mount
- True Talk™ Full Duplex Speaker Phone
- FCC registered
- Built in four number dialer
- Two visual call progress indicators
- Automatic number identifier
- Tone feature for patron signaling
- Two programmable auxiliary outputs
- Remotely programmable
- One or two programmable messages
- Programmable ring count
- Phone line monitoring available

The T2100 Series of emergency telephones are designed to withstand the rigors of harsh weather and environments, with electronics sealed with a Mil-Spec protective coating and protected speaker and microphone openings. They can be connected to analog telephone lines from any CO, PBX or key systems, or integrated into VOIP systems through a VOIP gateway.